

ER2 Series

SATA 6 Gb/s SSD

Key Features

- End-to-End Data Protection
- Thermal Throttling/Sensor
- Power Loss Protection
- High I/O & Throughput
- Performance
- Hot Pluggable
- Inrush Current Management
- ROHS-Compliant
- AES-256
- Smart Command Set



Model	ER2 Series
Configuration	
Capacity ¹	240GB~1920GB
Interface	SATA 6 GB/s
Form Factor	M.2 2280 / 2.5"
Performance	
Sequential Read / Write ¹ (Max.)	520/520 MB/s
4K Random Read / Write ¹ (Max.)	90K/45K IOPS
Latency Read/Write ¹ (Min.)	36/36 μ s
Reliability	
End-to-End Protection	Support
Power Loss Protection	Support
MTBF ²	>3 million hours
Endurance	
DWPD(for 5 years)	≥ 1
Power Consumption	
Idle	1.2 W
Read/Write(Max.)	4.5/5 W
Environment (Temperature)	
Non-Operating Temperature	-40 to 85°C

¹ Based on internal testing, performance, may vary depending on host device, OS and application

² MTBF - Mean Time Between Failures based on parts stress analysis

All information provided here is subject to change without prior notice.

Ordering Information

Operating Temperature	Form Factor	Capacity (GB)	Model Name*
Standard Temp.(0°C to 70°C)	M.2 2280	240/ 480	ER2-GDxxx
	2.5"	240/ 480/ 960/ 1920	ER2-CDxxx

*xxx = density (ex.240GB=240)



Solid State Storage Technology Corporation (SSSTC) is a global leader in the design, development, and manufacturing of Solid State Drives (SSDs). SSSTC offers customized solutions to PC Client, Industrial Solutions, Enterprise/Data Center, and Cloud and Edge Computing markets.
www.ssstc.com

12F, 392, Ruey Kuang Road, Neihu, Taipei 114, Taiwan R.O.C
www.ssstc.com/contact
 +886-2-8798-2886
 +886-2-5581-0868